



CUT LEVEL 5 NITRILE DIPPED GLOVES

ULTIMATE DURABILITY. ALL DAY COMFORT.

EN388



4X44E



| EN388 STANDARDS | | | | | | |
|----------------------------|---|---|---|---|---|----|
| Abrasion | 1 | 2 | 3 | 4 | - | - |
| Cut Resistance (Coup Test) | 1 | 2 | 3 | 4 | 5 | X* |
| Tearing | 1 | 2 | 3 | 4 | - | - |
| Puncture | 1 | 2 | 3 | 4 | - | - |
| Cut Resistance (TDM Test) | A | B | C | D | E | F |

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

**SMARTWIPE™ Touch
Screen Compatible
Fingertips & Palms**

**High Dexterity
Fingertips**

**Double Dipped
Nitrile Grip**
For protection
and durability

Breathable Back

**Best-in-Class
Puncture Resistance**

Color-Coded Bands
Easy cut level
identification



SPECIFICATIONS

| | |
|----------------|---------------------------|
| Gauge | 13 |
| Liner Material | Nylon and HPPE Blend Knit |
| Dip Material | Nitrile |
| Cuff Style | Elasticated Knit |

RECOMMENDED APPLICATIONS

- Metal Handling
- Abrasive/Sharp Materials
- Oily & Wet Conditions
- Pipe Threading
- Cutting
- Glass Handling
- Duct Work

CARE INSTRUCTIONS

Machine wash warm water (105°F),
mild detergent, no bleach.
Line dry.

| SIZE | 1 PAIR | 12 PAIR (Contractor Pack) |
|------|------------|---------------------------|
| S | 48-22-8950 | 48-22-8950B |
| M | 48-22-8951 | 48-22-8951B |
| L | 48-22-8952 | 48-22-8952B |
| XL | 48-22-8953 | 48-22-8953B |
| XXL | 48-22-8954 | 48-22-8954B |

**SEE
MORE
PPE**



or visit <https://qr.mke.tl/2qm6s>